





# DIN 1460 REFORZADO

## HEAVY DUTY



Anillo circular sobre eje

Anillo circular en ranura

Todas las dimensiones en mm

Eje	Ranura (G)					Anillo (F)											Wt. (lb/k)	
S	G	Tol.	W	Tol.	n (mínimo)	d	t	Tol.	D	Tol.	C	C1	L (máximo)	b	h (mínimo)			
12	11.5		1.60		0.7	0.25	1.50		11.0		19.3	18.3	3.4	1.8	1.7	0.75	17.500	1.130
15	14.3		1.60		1.1	0.35	1.50		13.8	+0.10	25.1	23.9	4.8	2.0	2.0	1.10	21.900	2.260
16	15.2	+0.00	1.60		1.2	0.40	1.50		14.7	-0.36	26.5	25.2	5.0	2.5	2.0	1.19	23.400	2.410
17	16.2	-0.11	1.60		1.5	0.40	1.50		15.7		27.5	26.2	5.0	2.6	2.0	1.39	24.800	3.200
18	17.0		1.60		1.5	0.50	1.50	0,06	16.5		28.7	27.2	5.1	2.7	2.0	1.56	26.300	4.070
19	17.8		1.60		1.8	0.60	1.50		17.5	+0.13	29.9	28.2	5.2	2.5	2.0	1.45	27.800	4.300
20	19.0	+0.00	1.85		1.5	0.50	1.75		18.5	-0.42	31.5	30.0	5.5	3.0	2.0	2.19	34.100	4.150
22	21.0	-0.13	1.85		1.5	0.50	1.75		20.5		34.5	33.0	6.0	3.1	2.0	2.42	37.500	4.980
23	21.8	+0.00	1.85		1.8	0.60	1.75		21.3		35.7	34.0	6.1	3.2	2.0	2.60	39.200	5.200
24	22.9		1.85		1.7	0.55	1.75		22.2		37.1	35.5	6.3	3.2	2.0	2.76	40.900	5.880
25	23.9		2.15		1.7	0.55	2.00		23.2		38.3	36.7	6.4	3.4	2.0	3.59	48.700	6.130
26	24.4	+0.00	2.15		2.4	0.80	2.00		23.6	+0.21	39.7	37.6	6.6	3.3	2.0	3.65	50.600	7.840
27	25.5	-0.21	2.15		2.3	0.75	2.00		24.7	-0.42	40.5	38.5	6.5	3.4	2.0	3.85	52.600	7.630
28	26.6		2.15		2.1	0.70	2.00		25.9		41.5	39.6	6.5	3.5	2.0	4.25	54.500	8.440
29	27.6		2.15		2.1	0.70	2.00		26.9		42.5	40.6	6.5	3.8	2.0	4.30	56.500	7.650
30	28.6		2.15		2.1	0.70	2.00		27.9		43.5	41.6	6.5	4.1	2.0	5.35	58.400	9.610
32	30.3		2.15		2.6	0.85	2.00		29.6		45.5	43.3	6.5	4.1	2.5	5.85	62.300	10.200
33	31.3		2.15	+0.14	2.5	0.85	2.00	+0.00	30.5		46.9	44.7	6.7	4.0	2.5	5.20	64.300	10.600
34	32.3		2.65	-0.00	2.6	0.85	2.50	-0.07	31.5	+0.25	47.9	45.7	6.6	4.2	2.5	7.05	82.800	12.200
35	33.0		2.65		3.0	1.00	2.50		32.2	-0.50	48.9	48.4	6.7	4.2	2.5	7.20	85.200	13.200
36	33.8		2.65		3.3	1.10	2.50		33.0		49.9	47.2	6.7	4.2	2.5	7.50	87.600	14.900
38	36.0	+0.00	2.65		3.0	1.00	2.50		35.2		52.1	49.6	6.8	4.3	2.5	8.30	92.500	15.800
40	37.5	-0.25	2.65		3.8	1.25	2.50		36.5		55.0	51.5	7.0	4.4	2.5	8.60	80.900	18.800
42	39.5		2.65		3.8	1.25	2.50		38.5		57.4	53.9	7.2	4.5	2.5	9.30	84.900	19.800
45	42.5		2.65		3.8	1.25	2.50		41.5	+0.39	61.0	57.5	7.5	4.7	2.5	10.70	91.000	21.200
48	45.5		2.65		3.8	1.25	2.50		44.5	-0.90	64.6	61.1	7.8	5.0	2.5	11.30	97.100	22.600
50	47.0		3.15		4.5	1.50	3.00		45.8		67.0	63.0	8.0	5.1	2.5	15.30	121.000	28.300
52	49.0		3.15		4.5	1.50	3.00		47.8		69.4	65.4	8.2	5.2	2.5	16.60	126.000	29.400
55	52.0		3.15		4.5	1.50	3.00	+0.00	50.8		73.0	69.0	8.5	5.4	2.5	17.10	133.000	31.100
58	55.0		3.15		4.5	1.50	3.00	-0.08	53.8		76.6	72.6	8.8	5.6	2.5	18.90	141.000	32.800
60	57.0	+0.00	3.15		4.5	1.50	3.00		55.8		79.0	75.0	9.0	5.8	2.5	19.40	146.000	33.900
65	62.0	-0.30	4.15		4.5	1.50	4.00		60.8	+0.46	84.6	80.6	9.3	6.3	3.0	29.10	210.000	36.800
70	67.0		4.15		4.5	1.50	4.00		65.5	-1.10	90.0	86.0	9.5	6.6	3.0	35.30	226.000	39.600
75	72.0		4.15		4.5	1.50	4.00		70.5		95.4	91.4	9.7	7.0	3.0	39.30	243.000	42.400
80	76.5		4.15		5.3	1.75	4.00	+0.00	74.5		100.6	96.1	9.8	7.4	3.0	43.70	259.000	52.800
85	81.5		4.15		5.3	1.75	4.00	-0.10	79.5		106.0	101.5	10.0	7.8	3.5	48.50	275.000	56.100
90	85.5	+0.00	4.15		5.3	1.75	4.00		84.5		111.4	106.9	10.2	8.2	3.5	59.40	291.000	59.400
95	91.5	-0.35	4.15		5.3	1.75	4.00		89.5	+0.54	116.6	112.1	10.3	8.6	3.5	61.20	307.000	62.700
100	96.5		4.15		5.3	1.75	4.00		94.5	-1.30	122.0	117.5	10.5	9.0	3.5	71.60	324.000	66.000

Con fondo amarillo se mantiene stock

